



Surface Velocity Radar for Measuring Open Channel Flow

- Usage Type Fixed installation
- Product Highlights Identify data influenced by sensor movement (e.g., wind, traffic) using meta data from integrated vibration and tilt sensors
- Application fields Non-contact surface velocity radar
- Internal data logger No
- Measurement range 0.08 ... 15 m/s (0.26 ... 49 ft./s)

OTT SVR 100 is a simple, non-contact, compact surface water velocity radar sensor. Designed for measuring flow in open channels and rivers where reliable velocity data is required continuously, during floods or periods of high concentrations of suspended sediments.

The sensor is mounted above the water surface, away from floating debris using a flexible bracket for vertical or horizontal installation. Velocity measurements and sensor status information from the integrated vibration and tilt sensor is available via SDI-12 over RS-485 and Modbus. It is also compatible with OTT Prodis 2 software for system calibration.









Technical Data OTT SVR 100



Measurement device for	Contactless velocity measurement
Measurement Range	0.08 15 m/s (0.26 49 ft./s)
Resolution	0,1 mm/s , (0.0001 ft)
Accuracy	± 2% of measured value
Radar opening angle	12° Azimuth
	24° Elevation
Detection distance	1 50 m (3.3 164 ft.)
Distance to water	0.5 25 m (1.64 82 ft.)
Radar frequency	24 GHz (K-band)
Interfaces	
Serial Interfaces	SDI-12, RS-232, RS-485
Protocols	SDI-12, MODBUS
Power supply	9 27 VDC
. ewe. supply	3 27 1 30
Power/current consumption	
active	typ. < 112 mA at 12 VDC
Maximum Current	< 250 mA
Dimensions	
Dimensions	124 F v 114 F v 00 mm /F 2 v 4 F v 2 2 in) (with out mounting
(LxWxH)	134,5 x 114,5 x 80 mm (5.3 x 4.5 x 3.2 in) (without mounting bracket)
Material	bideketj
Housing	ASA & Aluminium
Radom	TFM PTFE
Mounting	1.4301 (V2A)
Rotation range of swivel mount	Lateral axis: ±90 °
	Longitudinal axis: ±15 °
Carla La varib	10 (22 0 4)
Cable length	10 m (32.8 ft)
Weight	
with mounting bracket	820 g (1.81 lbs.)
without mounting bracket	1530 g (3.37 lbs.)
Temperature, in operation	-40° +85°C (-40° +185° F)
Housing	IP 68











